

7600



WITTENBORG

scanad™

Specifications

Height (adjustable)	1830 - 1850 mm
Width	700 mm
Depth	650 mm
Weight	185 - 190 kg (without ingredients)

Water Services

Cold water connection	¼"
Pressure (hot only versions)	0,8 - 10 Bar
Pressure (hot and cold versions)	1,5 - 10 Bar

Electrical Services

Voltage	230 V
Current	13 A fused
Frequency	50 Hz
Wattage (without cooling unit)	2 - 2.8 kW

Payment Systems

Compatible with all major coin and cashless systems. MDB, BDV and Executive protocols. Prepared for payment via a mobile phone.

Capacity

Cups (180 ml, 7C)	600
-------------------	-----

Ingredients

	Canister size	Capacity
Freshly ground coffee	12 l	5,0 kg
Freshbrew tea	12 l	4,9 kg
Freshly ground coffee (for DFB)	4/6 l	1,7/2,5 kg
Freshly ground tea (for DFB)	4/6 l	1,7/2,5 kg
Sugar	4/6 l	3,5/5,2 kg
Whitener/topping/milk	4/6 l	1,9/2,8 kg
Chocolate	4/6 l	2,3/3,5 kg
Instant coffee	4/6 l	2,3/3,5 kg
Instant cappuccino	4/6 l	1,1/1,7 kg
Lemon tea	4/6 l	3,2/4,9 kg
Soup	4/6 l	3,2/4,9 kg
Tomato soup	4/6 l	2,5/3,7 kg

Configurations

Drink selections

	SFB Tea	SFB Coffee	DFB	Instant
Freshbrew Coffee		•	•	
Instant Coffee 1		•		•
Espresso		•	•	•
Instant Coffee 2		•		•
Cappuccino		•	•	•
Espressochoc		•	•	•
Chocomilk		•	•	•
Freshbrew Tea	•		•	
Instant Tea		•		•
Chocolate		•	•	•
Hot water		•	•	•
Soup		•	•	•
Cappuccino (IN1)		•	•	
Espressochoc (IN1)		•	•	
Cappuccino (IN2)		•		•
Espressochoc (IN2)		•		•

Optional cold drink selections

	OE	OE	OE	OE
Syrup 1 Still / Carbonated	OE	OE	OE	OE
Syrup 2 Still / Carbonated	OE	OE	OE	OE
Cold powder Still / Carbonated	OE	OE	OE	OE
Cold water Still / Carbonated	OE	OE	OE	OE

* Instant model uses topping, rather than whitener in coffee drinks
* Extra sugar and extra whitener options available
OE: Optional Extra

Accessories

Hygiene kit · Cooling unit for cold beverages · Water filter · Option of different posters · Programmable · Rielda security lock · Lamp in cabinet.

All details of weight, capacity and dimensions are approximate and are intended for guidance only. The list of beverage selections is not exhaustive.

A space of at least 12 cm must be allowed between the back of the machine and the wall. For installation instructions, please refer to the Service Manual.

**GREENER
BY NATURE**

Presented by:



N&W WITTENBORG

N&W GLOBAL VENDING LIMITED • PO Box 25,
Dudley Street • Bilston • West Midlands • WV14 0LF
Tel: +44 (0) 1902 355000 • www.nwglobalvending.co.uk

Designed with your good taste in mind

Everybody appreciates a coffee break. Especially when it gives them the opportunity to get their hands on a lovely cup of delicious, freshly brewed coffee or tea. That's why we're offering our modern, innovative 7600 hot drinks machine, which is available in different tasteful versions: freshbrew coffee and tea, double freshbrew and instant coffee. It will be at home in any hard-working environment where coffee is appreciated.

Attractive and user-friendly

Wittenborg's 7600 model perfectly unites aesthetics and functionality and takes everything into account: the situation of use, maintenance and cleaning and the visual design – making the machine an attractive element of a busy workday.

Capacity with innovative contents

The machine's beautiful Scandinavian design conceals an ingenious, functional coffee brewing concept that uses the latest vending technology for making the best cup of coffee. A simple ergonomic design with easy access to every part, as well as colour coded cleaning parts and smooth surfaces make the machine easy to maintain and quick to refill.

Drinks to suit all tastes

You can look forward to your next coffee break! Because Wittenborg's 7600 model dispenses a total of 600 cups of unrivalled coffee, tea and chocolate as well as a wide selection of special beverages based on freshbrew and instant coffee – to fulfil even your hottest wishes in the next coffee break.

- We lead the way with lean, green production processes
- Avex 2007 Awards Best Sustainability award
- Vending Paris 2008 Awards Best Sustainable Development & the Environment
- We apply Life Cycle Product Design
- We adhere to a stringent Environmental Management System
- We adopt product Life Cycle Assessment
- We're proud to be a member of the EMP committee

7600



The 7600 reveals its functionally designed interior of smooth surfaces, clear colour codes and easy access to all serviceable parts. This ensures easy, quick and effective cleaning and maintenance.



The big ingredient canisters have a handle, so they are easy to pull out and refill. The lid opens automatically and the containers can be filled quickly and easily, either directly in or outside of the machine.



Optimum ease of use is in focus. From the simple drinks selection to the large, open dispensing area with a unique cup lift, easy cup removal, and the option of brewing directly into jugs up to 23.8 cm high.



Our innovative water and mixing system is patented and increases the machine's operating time, minimises the number of service visits and ensures top-quality beverages.



The 7600 from Wittenborg is truly a vision of modern vending technology: from the large poster area to the selection panel with its LCD display of 4 rows of 20 characters.

The large and easy-to-read drinks menu, guides the user through the many beverage options to the simple numeric selection panel. If required, the drinks can be dispensed directly to the users own cup or a jug.

The impressive capacity, the flexible configuration options, the programmable cleaning cycles and the optimised refill and maintenance features of the 7600 make it ideal for every office or production environment, canteens, public spaces or anywhere requiring quality, economy of scale and reliable, user-friendly serving. With the possibility of installing a coin mechanism, cashless system or being set up together with other vending machines from Wittenborg's 7000 line, it fulfils every dream of a modern coffee solution – to suit every taste!

The elegant, stylish design of the 7600 is promoted by two different posters that provide inviting alternatives for advertising the tempting coffee tastes awaiting the users.

